

## International Chassis

### HV607 Series Two Door Cab

- Seating for 2 (Air ride both seats)
- Two-Tone Color Paint
- Heated and Remote Mirrors

### Drive Train

- Cummins L9 450HP Engine
  - Engine Brake with 3 position settings and on/off switch
  - Heated fuel water separator
  - 2017 EPA Compliant with DEF tank and accessories
- Allison 3000 EVS Transmission
- Spicer 1710 Drive Line

### Frame/Undercarriage

- Double Rails
- Corrosion Resistant E-Coat coating for frame rails
- 269-inch Wheelbase

### Axles/Suspension

- Meritor MFS-16 16,000-pound front axle
- Shock Absorbers
- Leaf suspension rated at 16,000 pounds
- Meritor RT-46-1160 46,000-pound rear axle
- Hendrickson HAS-460-55 46k lb. capacity rear suspension (Air Ride)

### Brakes

- Anti-lock Braking, Automatic Traction Control, and Electronic Stability Control
- 16.5 x 6 drums front
- 16.5 x 7 drums rear

### Tires and Wheels

- Accuride Aluminum Rims
- Stainless Steel Wheel Trim
- Goodyear G289 tires front
- Goodyear RSD tires rear

### Cab Interior

- HVAC System
- AM/FM Radio
- Antenna mount and Co-ax cable

## TOYNE BODY

### Pump House

- All Stainless construction to include frame work
- Side mount panel
- Separate module from the body and cab

### Pump

- Hale MBP 1000 GPM (PTO)
- Mechanical seal
- Three sacrificial pump anodes
- Trident priming system

### Intakes

- Two (2) 6" side master Intakes
- Two (2) side 2 ½ inch aux. intakes

### Plumbing and Valves

- All stainless-steel plumbing or high-pressure hose with stainless ends
- Galvanized Victaulic couplings
- Akron 8000 series valves with stainless balls
- 10-year warranty on plumbing and valves

### Discharges

- Two (2) 2 ½ discharges on the officer's side panel
- Two 2 ½ discharges drivers side panel
- Two (2) 1 ¾ pre-connected crosslays

### Water Tank and Foam Cell

- 3000 Gallon water tank
- 3-inch tank to pump line
- 10" Newton swivel dump with electric actuation
- Two (2) 2 ½" Fireman's Friend direct tank fills

### Toyne Body

- Hot-dipped galvanized Structural Steel sub frame with 36k psi yield strength
- 304 Bolted Brushed Stainless body with #4 polished finish
- Stainless fenderettes
- 20 year structural and corrosion warranty for sub-frame
- 20 year structural and corrosion warranty for body
- 1000-pound capacity for all compartments
- Stainless steel hinged doors
- 24" rear step

### Compartments

- Low height compartments both sides.
- 71" wide front compartments and 32" rear compartments.
- Through the rear suction hose and ladder storage compartments
- Two full height LED strip lights per compartment

### Storage Items

- 2 roll out trays
- Zico electric/hydraulic port-tank rack with suction hose storage tray

### Body Electrical

- Weldon Multi-Plex System
- LED under body lights
- All DOT and Step Lighting to be LED
- Whelen LED Back-Up, Turn and brake lights

### Scene Lighting

- Hi-Viz 14k lumen brow light
- Six Akron Revel LED body lights (side and rear lights activate when truck is in reverse)

### Emergency Lighting

- Whelen 55" LED Freedom light bar
- Two Whelen LED mini bars at the rear upper of body
- Whelen M6 lower level warning lights

### Audible Emergency Warning

- Whelen 295HFS electric siren
- Two Grover airhorns
- Federal "Q"

### Misc. Items

- Two (2) lengths of 6" x 10' Kochek suction hose
- 24,14, and 10; ladder package
- Wheel Chocs
- Lettering and striping
- Delivery and training